

# EGT6242NVK BI Hob





### The power of gas meets the beauty of glass

This sleek gas-on-glass hob combines the precision and efficiency of a gas flame with glossy, elegant and easy-to-clean ceramic glass - a unique design experience.



# A natural movement, all the way from low heat to high

At the front of this hob are the rotary control knobs. They're designed to be easy to twist and turn when you change the power levels of your hob.



# A new level of flexibility for using pans of different sizes

Because this hob has three different sizes of burner, it gives a new level of flexibility for using your different-sized pots and pans more effectively.

#### More Benefits:

- · Automatic hob ignition allows you to get started without delay
- Automatic gas cut-off a practical solution for peace of mind

### Features:

- · Hob type: Gas on Glass
- Rotary knob controls
- •Controls position: Front Middle
- •Left front zone: Auxiliary Burner , 1000W/54mm
- •Left rear zone: Rapid Burner , 2900W/100mm
- •Right front zone: Semi Rapid Burner , 1900W/70mm
- •Right rear zone: Semi Rapid Burner , 1900W/70mm
- Integrated electric ignition through control knob
- •Gas safety thermocouples: gas is cut off at source if the flame fails
- Enameled pan supports
- Gas conversion kit
- •Main colour: Black

## **Technical Specs:**

- Product Installation : Built\_In
   Product Typology : Gas\_Hob
   Product Classification : Performance
- •Installation : Independent
- •Size: 60
- •Hob type : Gas On Glass •Design family : BlueFire •Main colour : Black
- •Control Panel material : Glass
- •Frame type : None •Knobs colour : Black
- •Top Control Place : Front Middle
- •Type of controls : Knobs •Control function : No
- •Other comments design : Black knobs
- •Width mm: 590
  •Depth mm: 520
  •Built in height mm: 47
  •Width cutting: 560
  •Depth cutting: 480
  •Fastening: Fixing Clamps
  •Gas original: G20 (2H) 20 mbar
- •Gas replacement 2: G30/G31 (3B/P) 28-30 mbar, With Additional

Injectors

- •Gas replacement 3 : None •Gas category : II2E+3+, II2H3B/P
- •Frequency: 50/60 •Voltage: 220-240 •Cord length external: 1.1 •Type of plug: None
- •Connector type : Cylinder gas elbow
- •Iginition: On Control Knob •Hob safety: Thermocouple •Programmed plate: No •Hob pan support: 4, Enamel
- •Hob lid : No
- •Residual heating indicators : No

# **Product Description:**

Electrolux949 640 423